



Model	Dimensions (mm)	
	"L"	"E"
FD4-050	50	25
FD4-100	100	50
FD4-150	150	25
FD4-200	200	50
FD4-250	250	25
FD4-300	300	50
FD4-350	350	25
FD4-400	400	50
FD4-450	450	25
FD4-500	500	50

The foregoing presentation is a non-binding concept for presentation only, submitted for the purpose of soliciting business. Any and all items are changeable and reconfigurable. All data, ideas, concepts, specifications, designs and other pertinent product definitions are proprietary to NUTEC. They are submitted to the recipient in confidence. NUTEC retains all intellectual property rights to product design and concept. Deer Park - New York October 2003

NUTEL®

FLEXDRIVE 4

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE:

0 PL. DECIMALS (X) ± .5 mm	APPROVALS	DATE
1 PL. DECIMALS (X.X) ± .1 mm	DRAWN	YY 8/6/10
2 PL. DECIMALS (X.XX) ± .05 mm	CHECKED	RHS
ANGLES ± 1/2°	ISSUED	

MATERIAL: _____
FINISH: _____

PROJECT NO. _____
DWG NO. FD4
SCALE 0.6
SHEET 1 OF 1

* LAST HOLES COULD BE 50 OR 25. SEE "E" ON TABLE

Ø5.3

Ø5-H8 2PLCS

Ø5-H7 2PLCS

M5 2x2PLCS

100

45 45 120

47

L-7

L/2

50 50 50 50 50

0.005

0.005